

EXCLUSIVELY FOR INDUSTRIAL & INSTITUTIONAL USE

**BRITE KOTE E-24
METAL INTERLINKING
FLOOR FINISH**

Tough metal crosslinked floor finish bonds to the floor. Does not scuff up or walk off. The metal interlinking system assures a tough coat that will not powder. The extreme strength of polymer-metallic bonding provides for easy maintenance and assures a beautiful floor with minimum care.

Product Code 6020
To Reorder Call (281) 647-9700 or
1-800-295-BETA

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
P.O. BOX 218686
HOUSTON, TX 77218



Brite Kote E-24

Metal Interlinking Floor Finish

- *Self Leveling* • *Non-Powdering*
- *Durable Daily Cleaning Formulation*
- *Superior Bonding*
- *Impervious to Scuffing*
- *Resists Black Heel Marks*

NET CONTENTS:

6 20 30 55 GALLONS

KEEP OUT OF REACH OF CHILDREN
CAUTION:
See Additional Cautions On Side Panel

DIRECTIONS FOR USE

Clean floor thoroughly. Rinse with clear water and let dry. If floor has been stripped, use a sealer to fill pores, renew colors and establish a foundation for this finish. Apply in thin even coats with a clean mop. Let each coat dry completely before recoating. Apply 2 to 3 coats. For wet look finish, buff with a high speed buffer.

CAUTION

Keep out of reach of children. Harmful if swallowed. May cause irritation to eyes or skin. If in eyes, flush thoroughly with water and contact physician. If swallowed, give water and contact physician. For Industrial Use Only.

HMIS Codes: Health - 0, Flammability - 0, Reactivity - 0, Personal - A.

Made in USA